

PROJECT


CATALOG #

TYPE

# VERTA SERIES

## Indoor LED Grow Light

SpecGrade's powerful yet versatile Verta is perfect for both flowering and vegging in indoor applications. Its modular design allows you to change out the bars should you choose to switch the spectrum or increase the efficacy as technology evolves. The proprietary thermal management system radiates less heat onto the plants while at the same time delivering unprecedented light levels and uniformity. The standard 0-10V dimming functions can easily be utilized with the Grow-Connect-ready (daisy-chaining) wiring harness. The finely-tuned A1 for the Entire Life Cycle Spectrum has proven at universities and various grow environments to improve the trichomes and taste while cutting operational costs and shortening grow cycles.



### INTENSITY

Designed for maximum PPFd while using significantly less power than traditional lamps.

### PRECISION

Precision-Engineered A1 Spectrum Offers Light Tailored For a Plant's Entire Life Cycle

### ENGINEERING


Proprietary Thermal Management System Radiates Less Heat.

## Ordering Information


EXAMPLE PART #: VERTA - 4 - A1 - V01 - WT - 15FT

VERTA		A1		WT	15FT
SERIES	MODEL	SPECTRUM	INPUT VOLTAGE	POWDER COAT FINISH	CORD LENGTH
VERTA	4 8	A1	V01 (100-277V) V04 (347-480V)	WT (Standard)	15FT (Standard)

## Available Spectrums



A1 Spectrum | Entire Life Cycle  
Standard



S1 Spectrum | Entire Life Cycle  
Optional, No DLC

# VERTA SERIES

Indoor LED Grow Light

## Specifications

### Performance

PPF (± 5%)	
VERTA-4	750 μmol/s
VERTA-8	1,478 μmol/s

### System Power

VERTA-4	330W
VERTA-8	650W

Efficacy | 2.6 μmol/J

Distribution | 120°

Spectrum | A1

Thermal | 100% Passive

Expected Life | Q90 > 55,000 hrs.

### Materials

LEDs | Proprietary blend of Samsung, Lumileds and OSRAM chips

Frame | Powder Coated Stainless Steel

Finish | Polyester Powder Coat

Heat Sink | AL6061 Aluminum

### Electrical

Voltage | 100-277VAC (V01), 347-480VAC (V04)

Surge Protection | 4kV (V01), 6kV (V04)

Dimming | 0-10V Compatible

Power Factor | 0.999

Current THD | <5%

### Wiring Harness (Daisy-Chain)

Each light is Grow-Connect ready (standard).

Request information

### Listings

Rating | IP66

Safety | UL 8800, UL 1598, UL 8750

FCC Compliant | 47 CFR FCC Part 15 Subpart B

NEMA Rating | 4X

DLC | Listed - Horticultural QPL

### Misc

Geometry	Weight	Dimensions	FootPrint
VERTA-4	22.5 lbs	42" x 20" x 3.75"	24" x 48"
VERTA-8	43 lbs	42" x 42" x 3.75"	48" x 48"

Typical Mounting Height | ≥6" Above Canopy

Cord Length | 15-ft cord

Finish | White

### Warranty


LEDs | 7 Years

Drivers | 5 Years

### Electrical Standard

15' cord + plugs  
(NEMA 6-15P plus  
15P adapter)

### Standard Cord and Plug Configuration




Quick Connect Pigtail 15A  
Item: GCPT-AC (Power)  
Item: GCPT-DC (Dimming)

250V Side Blade 15A  
(NEMA 6-15P)  
Item: SBP

Adapter included to  
change the 250v to  
120V Straight Blade  
15A (NEMA 5-15P)  
Item: STDP




### Plug Option



277V Twist Lock Plug 15A  
(NEMA L7-15P)  
Item: STP

## Product Data

### Dimensions




Standard adjustable  
cabling allows for easy  
raising and lowering of  
grow light

### Maximum Amperage By Voltage Service


		8 BAR					
Voltage	120V	208V	240V	277V	347V	480V	
Amperage	5.57A	3.21A	2.78A	2.41A	1.92A	1.39A	

		4 BAR					
Voltage	120V	208V	240V	277V	347V	480V	
Amperage	3.0A	1.8A	1.6A	1.4A	1.1A	0.8A	

## Controls



### Wireless



### Hard-Wired

Due to continuous improvement and innovation, product appearance and specifications may change without notice. Actual performance may differ as a result of end-user environment and application.

TOLL-FREE: 888-410-5337 | FAX: 614-868-5344 | © 2020 SpecGradeLED

REV 10\_2022

www.SpecGradeLED.com