

VERTA SER Comparison	RIES					
Guide						
	VERTA-8F (920W)	VERTA-8F (820W)	VERTA-8	VERTA-6F (720W)	VERTA-6F (640W)	VERTA-4
Dimensions	42"x42"x3.75"	42"x42"x3.75"	42"x 42"x3.75"	42"x42"x3.75"	47"x42"x3.5"	42"x20"x3.75"
Efficacy	2.8 µmol/J (920 Watts)	2.8 µmol/J (820 Watts)	2.7 µmol/J (640 Watts)	2.8 µmol/J (720 Watts)	2.65 µmol/J (640 Watts)	2.5 μmol/J (330 Watts)
Intensity	2600 µmol/s	1800 µmol/s	1706 µmol/s	2050 µmol/s	1700 µmol/s	822 µmol/s
Modularity	•	•	•	•	•	•
Passive Thermal Management	4984 sq. In. of heat sink	4086 sq. in. of heat sink	2492 sq. in. of heat sink			
Superior Uniformity	2462 LED chips over 8-bars	2462 LED chips over 8-bars	2462 LED chips over 8-bars	2018 LED chips over 8-bars	2018 LED chips over 6-bars	1232 LED chips over 4-bars
Design Lights Consortium (DLC) Certification	•	Ø	•	•	•	Ø
UL8800 Certifcation	•			•	•	•
IP 66 Rating	•	Ø	•	•	•	•
Warranty	7-Year LED 5-Year Driver					
Grow-Connect Daisy-Chaining	•	②	②	Ø	Ø	Ø

www.SpecGradeLED.com | Call us: 888-410-5337